


Technical data sheet

M-iQ K-S54 P6

Execution for: Hong Kong



Schematic sectional view of machine

Rack type dishwashing machine

Working direction: left - right

Power supply: 3N PE 380V 50Hz

Heating: Electric

Fresh water final rinse: Soft cold water

Technical data

Performance*) (DIN SPEC 10534)	Contact time	2 minutes
	Transport speed (DIN)	0.78 m/min
	Rack capacity (DIN)	95 racks/h
	Transport speed (max.)	1.05 m/min
	Rack capacity (max.)	128 racks/h
Motors and controls	Total	4.9 kW
Heating energies	Total	28.5 kW
Consumption**	Average consumption during typical operation	25.4 kW
Electrical feeding cable	Power supply	3N PE 380V 50Hz
	Total connected load	33.4 kW
	max. rated current	57.3 A
	Max. Elect. cable cross-section	35 mm ²
Fresh water	Fresh water final rinse: soft cold water	165 l/h
Tank filling	Soft warm water	141 l
Regeneration	Regeneration water quantity	110 l/h
		(Included in 'fresh water,' see above)
Air outlet***	Exhaust air volume approx.	150 m ³ /h
	Exhaust air temperature approx.	22 °C
	Relative humidity approx.	90 %



The clean solution

Technical data sheet

Heat load****	total	5.8 kW
	perceptible	3.4 kW
	latent	2.4 kW

Dimensions of machine	Entry tunnel (E)	150 mm
	Wash tank (HWZ V)	800 mm
	Pump rinse section (P)	600 mm
	1. Drying section (TR)	0 mm
	Total	1550 mm

Equipment	Exhaust air heat recovery
------------------	---------------------------
